



**DON'T LIKE READING INSTRUCTIONS?
GO TO YOUTUBE.COM AND SEARCH
"ON TIME SHAKEDOWN INSTRUCTIONS"
FOR A COMPLETE INSTALLATION
INSTRUCTION VIDEO!**

SHAKEDOWN FEEDER INSTRUCTIONS

ITEM# 74000

SHAKEDOWN SET UP

STEP 1: Install the three "C" shaped metal feet that are included in your hardware packet. Take one 5/16 x 3/4 length bolt and insert in the hole of the foot bracket. Next insert the threaded portion of the bolt through one of the three mounting holes on bottom of the hopper. Once bolt is inserted, place the 3/4 metal washer over the bolt on the inside of the hopper. Now install the 5/16 locking nut. Use a 1/2 wrench or socket to tighten completely, and repeat steps for the other two feet.

STEP 2: Using a 3/8 wrench or socket tighten all three nuts on the feed plate until all three springs are completely collapsed. This is critical to keep from spilling of attractant, corn, etc until the unit is hung and ready to use. ****Do not over tighten!** When tightening these three nuts, tighten each nut three to four turns until the feed tray's springs are fully compressed. Do not fully tighten each nut one at a time. Work in a rotating fashion three to four turns for one, move to next and turn three to four times, etc. at an even rate until the springs are compressed.

STEP 3: Gently remove the hopper lid. Squeeze both sides of the white power plug and disconnect it. Set the lid aside.

STEP 4: Attach the hanger bracket. To attach the hanger bracket, take one of the 3/8" bolts and slide through the hanger bracket, then slide on one of the included rubber washers. Next insert the bolt and rubber washer through the hole on the side of the barrel. Place the metal fender washer then nut onto the bolt that is now extending into the inside of the barrel. Repeat on opposite side. Slowly tighten until the hanger bracket will remain vertical without assisting/holding it vertical but can still be pivoted over for refilling the unit.

STEP 3: Install battery. *NOTE. DO NOT USE HEAVY DUTY BATTERY. USE A HIGH QUALITY ALKALINE 6V LANTERN STYLE BATTERY SUCH AS ENERGIZER #529.* Remove the long bolt on the battery holder. Slide battery into position using a tilting motion. The negative battery spring will be inside the oval cut out. The positive terminal will be outside of the oval cut out near the digital timer. Once battery is in position reinstall the long battery holder screw. Connect the digital timer to the battery using the alligator clips. DO NOT CONNECT POWER CLIPS BACKWARDS. Connect the red alligator clip to the positive (+) battery spring. Connect the black alligator clip to the negative (-) battery spring. Again- Do not connect the power clips backwards.

FILLING THE FEEDER: Do not fill feeder until the unit is at location to be hung. Make sure the feet are on level ground. If connected, disconnect the white plug to remove the lid from the motor. Now you will be able to fill the unit with product. Once filled, you will reconnect the white plug and replace the lid. This unit can be filled with a custom mixture of your choice. It is very important to keep the unit level during filling.

NOTE: This unit does not dispense at the same rate of standard wildlife feeders. In most cases, a 3-4 second run time is a more than adequate length of time depending on the feed plate height adjustment.

You are now ready to program the timer and reattach lid. Timer setting and further set up instructions are on page 2.